



Pneumatic Hand Pump

Combination of Vacuum & Pressure

HP 40

Application

To be used along with analog or digital, standard or master, vacuum or pressure, gauges or indicator for checking and calibration of air operated sensors, manometers, gauges, indicators, controllers, transducers, transmitters, recorders and data loggers

Features

Compact, light weight & hand operated . Generates pressure and vacuum (user selectable) through hand operated scissor action pump . Vernier with fine adjustment enables precise setting . Recommended strictly for air / pneumatic applications only

SPECIFICATIONS

Range: Generation of Pressure: 40 Bar

Generation of Vacuum: 0.95 Bar

Medium: Dry Air

End Connection: 1/4" BSP (F) Test & Master

Weight: 1 Kg

Dimension: 240 mm (H) x 170 mm (W) x 60 mm (D)

Standard Delivery:

- 1 meter 4 mm Nylon hose with 1/4" BSP (F) adapter for connecting the test instruments
- Swivel Adapter with 'o' Ring- 1 no.
- User Manual
- Test Certificate

Optional Accessories:

- Set of Bonded Seals 1/8" - 3 Nos.
- Set of Nylon Washers: 1/8", 1/4", 3/8", 1/2" - 5 Nos. each
- Set of Adaptors:
 - 1/4" BSP (M) x 1/8" BSP (F), 1/8" NPT (F), 1/4" NPT (F),
 - 3/8" BSP (F), 3/8" NPT (F), 1/2" BSP (F), 1/2" NPT (F) - 1 no. each
- Quick Coupling & Connector - 1 No.



Contact us for other ranges.

Manufacturer of
**TEST BENCHES
CALIBRATION INSTRUMENTS**

**ISO 9001
Certified Company**

www.rndinstruments.com

Contact

5, Natesan Nagar, Alapakkam,
Chennai 600116. Tamilnadu, INDIA.
Tel.: +91-44-4283 9039 / 4284 1119
Mobile Nos.: +91-7358393981 / 7358393984
email: sales@rndinstruments.com
quote@rndinstruments.com

ACCREDITED CALIBRATION LABORATORY

As per ISO / IEC 17025

**THERMAL
MECHANICAL
ELECTROTECHNICAL**

www.calibrationlab.in