



Pneumatic Hand Pump

Combination of Vacuum & Pressure

HP 2

Application

To be used along with analog or digital, standard or master, vacuum or pressure, gauges or indicator for checking and calibration of air operated sensors, manometers, gauges, indicators, controllers, transducers, transmitters, recorders and data loggers

Features

Compact, lightweight & hand operated, Generates pressure as well as vacuum (user selectable), thro' hand operated scissor action pump, Vernier with fine adjustment enables precise setting, Recommended strictly for air / pneumatic applications only



SPECIFICATIONS

Range: Generation of Pressure: 2 Bar
Generation of Vacuum: 0.850 Bar

Medium: Dry Air

End Connection: 1/4" BSP (F) Test & Master

Weight: 800 grams

Dimension: 235 mm (H) x 180 mm (W) x 65 mm (D)

Standard Delivery:

- 1 meter 4 mm Nylon hose with 1/4" BSP (F) adapter for connecting the test instruments
- User Manual
- Test Certificate

Optional Accessories:

- Set of Bonded Seals 1/8" - 3 Nos.
- Set of Nylon Washers: 1/8", 1/4", 3/8", 1/2" - each 5 nos.
- Set of Adaptors:
1/4" BSP (M) x 1/8" BSP (F), 1/8" NPT (F), 1/4" NPT (F),
3/8" BSP (F), 3/8" NPT (F), 1/2" BSP (F), 1/2" NPT (F) - 1 No. each
- Quick Coupling & Connector - 1 No.

Manufacturer of
**TEST BENCHES
CALIBRATION INSTRUMENTS**

**ISO 9001:2008
Certified Company**

www.rndinstruments.com

Contact

5, Natesan Nagar, Alapakkam,
Chennai 600116. Tamilnadu, INDIA.
Tel.: +91-44-4283 9039 / 4284 1119
Mobile Nos.: +91-87544 78464 / 87544 68463
email: sales@rndinstruments.com
service@rndinstruments.com

ACCREDITED CALIBRATION LABORATORY

As per ISO / IEC 17025

**THERMAL
MECHANICAL
ELECTROTECHNICAL**

www.calibrationlab.in