



Pneumatic Hand Pump

Combination of Vacuum & Pressure

HP 25

Application

To be used along with analog or digital, standard or master, vacuum or pressure, gauges or indicator for checking and calibration of air operated sensors, manometers, gauges, indicators, controllers, transducers, transmitters, recorders and data loggers

Features

Compact, light weight & hand operated . Generates pressure and vacuum (user selectable) through hand operated scissor action pump . Vernier with fine adjustment enables precise setting . Recommended strictly for air / pneumatic applications only

SPECIFICATIONS

- Range:** Generation of Pressure: 25 Bar
 Generation of Vacuum: 0.850 Bar
- Medium:** Dry Air
- End Connection:** 1/4" BSP (F) Test & Master
- Weight:** 700 grams
- Dimension:** 235 mm (H) x 140 mm (W) x 65 mm (D)

Standard Delivery:

- 1 meter 4 mm Nylon hose with 1/4" BSP (F) adapter for connecting the test instruments
- User Manual
- Test Certificate

Optional Accessories:

- Set of Bonded Seals 1/8" - 3 Nos.
- Set of Nylon Washers: 1/8", 1/4", 3/8", 1/2" - 5 Nos. each
- Set of Adaptors:
 - 1/4" BSP (M) x 1/8" BSP (F), 1/8" NPT (F), 1/4" NPT (F),
 - 3/8" BSP (F), 3/8" NPT (F), 1/2" BSP (F), 1/2" NPT (F) - 1 no. each
- Quick Coupling & Connector - 1 No.



The Information given in this document is subject to change due to continuous improvement without notice. All Rights Reserved by R&D Instrument Services, Chennai, India.

Contact us for other ranges.

Manufacturer of
**TEST BENCHES
 CALIBRATION INSTRUMENTS**

**ISO 9001:2008
 Certified Company**

www.rndinstruments.com

Contact

5, Natesan Nagar, Alapakkam,
 Chennai 600116. Tamilnadu, INDIA.
 Tel.: +91-44-4283 9039 / 4284 1119
 Mobile Nos.: +91-87544 78464 / 87544 68463
 email: sales@rndinstruments.com
service@rndinstruments.com

ACCREDITED CALIBRATION LABORATORY

As per ISO / IEC 17025

**THERMAL
 MECHANICAL
 ELECTROTECHNICAL**

www.calibrationlab.in