



Dry Block Temperature Calibrator

1200T



Application

Ideal for calibration of thermocouples, RTD, gauges, thermometers, switches, transmitters, etc.

Features

Dry Block . Fast Heating (60 mins.) & Cooling (45 mins. through forced air) . Controlled through PID Controller . Good Stability . Power Supply for Transmitters . Facility to check Temperature Switch Test

Technical Specification

Range*	: 300 to 1200 °C
Resolution	: 1°C
Accuracy	: ±3°C
Units	: °C / °F (Switchable)
Stability	: ±1°C
Insertion Depth	: 150 mm
Power Supply	: 230 VAC ±5%, 2 KW
Switch Test Supply	: 5 Volt DC Nominal
Display	: LED
DC Output	: Transmitter Power Supply

*Best range recommended shall be 500°C - 1200°C



Multi Hole Insertion Tube



Standard Delivery

1. Instrument : 1 no.
2. Power Cable : 1 no.
3. Test Lead (2 wire) : 1 no.
4. Multi Hole Insertion Tube :
1x25 mm+ 2x7 mm + 2x4 mm
(Please consult us for other sizes)
5. Insertion Tool : 1 no.
6. Spare Fuses : 500 mA, 6A, 10A - 2 nos.
7. Insulator
8. User Manual : 1 no.
9. Traceable Calibration Certificate

Optional

- Custom Built Insertion Tube
- Accredited (NABL) Calibration Certificate as per ISO/IEC 17025 Standard

Manufacturer of
TEST BENCHES
CALIBRATION INSTRUMENTS

ISO 9001
Certified Company

www.rndinstruments.com

Contact

5, Natesan Nagar, Alapakkam,
Chennai 600116. Tamilnadu, INDIA.
Tel.: +91-44-4283 9039 / 4284 1119
Mobile Nos.: +91-7358393981 / 7358393984
email: sales@rndinstruments.com
quote@rndinstruments.com

ACCREDITED CALIBRATION LABORATORY

As per ISO / IEC 17025

THERMAL
MECHANICAL
ELECTROTECHNICAL

www.calibrationlab.in