



Application

Ideal for calibration of vacuum & pressure gauges, switches, transmitters, etc.

Features

MEASUREMENTS: Electrical measurements of mA & Volts . Peak pressure measurements (High & Low peak)

PRESSURE SWITCH TEST FACILITY: Opening and closing pressures are easily identified by display hold while opening and closing contact

DISPLAY: Large backlit alpha numeric display with 2 lines (one line Pressure and second line for electrical measurement) . 'Auto OFF' function for longer battery life

KEYPAD: Feather Touch keypad for easy operation . Dedicated ZERO key for Zeroing before test



Specification

Model	Range*	Resolution	Accuracy	Selectable Pressure Units
EPC 2	-1 bar Vacuum to 2 bar	0.0001	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa, inH ₂ O, mmHg, mbar, cmH ₂ O
EPC 10	-1 bar Vacuum to 10 bar	0.001	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa, inH ₂ O, mmHg, mbar, cmH ₂ O
EPC 20	-1 bar Vacuum to 20 bar	0.001	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa, inH ₂ O, mmHg, mbar, cmH ₂ O
EPC 40	-1 bar Vacuum to 40 bar	0.001	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa, inH ₂ O, mmHg, mbar, cmH ₂ O
EPC 100	0 to 100 bar	0.01	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa, inH ₂ O, mmHg
EPC 200	0 to 200 bar	0.01	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa, inH ₂ O
EPC 400	0 to 400 bar	0.01	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa
EPC 700	0 to 700 bar	0.01	±0.05% F.S.	bar, kg/cm ² , MPa, mH ₂ O, atm, psi, inHg, ftH ₂ O, kPa

*Contact us for other ranges.

Over Pressure Alarm	: 20% of Full Scale upto 40 bar 5% of Full Scale for other ranges
Pressure Media	: Compatible to 316 Stainless Steel
Current Terminal Input	
Protection	: Fuse: 100mA / 250V
Display	: Alpha Numeric Display
Backlight	: LED Backlight
Power Supply	: Li-ion Rechargeable Battery
Low Battery Indicator	: Yes
Auto Power Off	: 15 minutes
Battery Backup	: 20 hours
Pressure Connection	: 1/4" BSP Female
Operating Temperature	: 10 to 50°C
Instrument Casing	: ABS Plastic
Instrument Dimensions	: 200 mm x 110 mm x 60 / 35 mm (LxWxD)
Instrument Weight	: 550 gms.

Measurements

Facility	Range	Resolution	Accuracy
mA	0 to 25 mA	0.001 mA	±0.025% of Reading + 3 µA
Volts	0 to 30 V	0.001 V	±0.025% of Reading + 3 mV

Accuracy specifications include effect of non-linearity, hysteresis and repeatability at 23±5°C

Standard Delivery

1. Instrument : 1 no.
2. Test Lead (2 wire) : 1 no.
3. Charger : 1 no.
4. User Manual : 1 no.
5. Traceable Calibration Certificate

Optional

Accredited (NABL) Calibration Certificate as per ISO/IEC 17025 Standard

Manufacturer of
TEST BENCHES
CALIBRATION INSTRUMENTS

ISO 9001
Certified Company

www.rndinstruments.com

Contact

5, Natesan Nagar, Alapakkam,
Chennai 600116. Tamilnadu, INDIA.
Tel.: +91-44-4283 9039 / 4284 1119
Mobile Nos.: +91-7358393981 / 7358393984
email: sales@rndinstruments.com
quote@rndinstruments.com

ACCREDITED CALIBRATION LABORATORY

As per ISO / IEC 17025

THERMAL
MECHANICAL
ELECTROTECHNICAL

www.calibrationlab.in